



Peilstabtablelle

DIN 6608 und DIN 6616

Nenninhalt: 30.000 Liter Tankdurchmesser: 2 000 mm - Gesamtlänge: 9 550 mm

| cm | Liter | cm | Liter | cm | Liter | cm | Liter |
|----|--------|-----|---------|-----|---------|-----|---------|
| 1 | 17.5 | 51 | 5986.3 | 101 | 15243.4 | 151 | 24398.9 |
| 2 | 49.5 | 52 | 6153.8 | 102 | 15436.4 | 152 | 24561.7 |
| 3 | 90.8 | 53 | 6322.4 | 103 | 15629.3 | 153 | 24723.2 |
| 4 | 139.6 | 54 | 6492.1 | 104 | 15822.2 | 154 | 24883.5 |
| 5 | 194.9 | 55 | 6662.9 | 105 | 16014.9 | 155 | 25042.4 |
| 6 | 255.9 | 56 | 6834.6 | 106 | 16207.6 | 156 | 25199.9 |
| 7 | 322.2 | 57 | 7007.4 | 107 | 16400.1 | 157 | 25356.1 |
| 8 | 393.2 | 58 | 7181.1 | 108 | 16592.4 | 158 | 25510.8 |
| 9 | 468.7 | 59 | 7355.8 | 109 | 16784.6 | 159 | 25664.0 |
| 10 | 548.4 | 60 | 7531.4 | 110 | 16976.6 | 160 | 25815.8 |
| 11 | 631.9 | 61 | 7707.8 | 111 | 17168.3 | 161 | 25966.0 |
| 12 | 719.2 | 62 | 7885.2 | 112 | 17359.8 | 162 | 26114.6 |
| 13 | 810.1 | 63 | 8063.3 | 113 | 17551.1 | 163 | 26261.6 |
| 14 | 904.3 | 64 | 8242.3 | 114 | 17742.0 | 164 | 26406.9 |
| 15 | 1001.8 | 65 | 8422.1 | 115 | 17932.6 | 165 | 26550.6 |
| 16 | 1102.3 | 66 | 8602.6 | 116 | 18123.0 | 166 | 26692.4 |
| 17 | 1205.9 | 67 | 8783.9 | 117 | 18312.9 | 167 | 26832.5 |
| 18 | 1312.3 | 68 | 8965.9 | 118 | 18502.5 | 168 | 26970.8 |
| 19 | 1421.4 | 69 | 9148.5 | 119 | 18691.7 | 169 | 27107.1 |
| 20 | 1533.3 | 70 | 9331.9 | 120 | 18880.5 | 170 | 27241.5 |
| 21 | 1647.7 | 71 | 9515.9 | 121 | 19068.8 | 171 | 27373.9 |
| 22 | 1764.7 | 72 | 9700.5 | 122 | 19256.7 | 172 | 27504.3 |
| 23 | 1884.1 | 73 | 9885.7 | 123 | 19444.1 | 173 | 27632.5 |
| 24 | 2005.8 | 74 | 10071.5 | 124 | 19631.0 | 174 | 27758.6 |
| 25 | 2129.8 | 75 | 10257.8 | 125 | 19817.4 | 175 | 27882.5 |
| 26 | 2256.0 | 76 | 10444.7 | 126 | 20003.2 | 176 | 28004.0 |
| 27 | 2384.4 | 77 | 10632.0 | 127 | 20188.4 | 177 | 28123.2 |
| 28 | 2514.9 | 78 | 10819.9 | 128 | 20373.0 | 178 | 28239.9 |
| 29 | 2647.4 | 79 | 11008.2 | 129 | 20557.1 | 179 | 28354.2 |
| 30 | 2781.9 | 80 | 11196.9 | 130 | 20740.5 | 180 | 28465.8 |
| 31 | 2918.4 | 81 | 11386.1 | 131 | 20923.2 | 181 | 28574.7 |
| 32 | 3056.7 | 82 | 11575.7 | 132 | 21105.2 | 182 | 28680.8 |
| 33 | 3196.9 | 83 | 11765.6 | 133 | 21286.5 | 183 | 28784.0 |
| 34 | 3338.8 | 84 | 11955.9 | 134 | 21467.1 | 184 | 28884.2 |
| 35 | 3482.5 | 85 | 12146.5 | 135 | 21646.9 | 185 | 28981.3 |
| 36 | 3627.9 | 86 | 12337.4 | 136 | 21825.9 | 186 | 29075.1 |
| 37 | 3774.9 | 87 | 12528.6 | 137 | 22004.1 | 187 | 29165.5 |
| 38 | 3923.6 | 88 | 12720.1 | 138 | 22181.5 | 188 | 29252.3 |
| 39 | 4073.8 | 89 | 12911.9 | 139 | 22358.0 | 189 | 29335.4 |
| 40 | 4225.6 | 90 | 13103.8 | 140 | 22531.6 | 190 | 29414.4 |
| 41 | 4378.9 | 91 | 13296.0 | 141 | 22708.3 | 191 | 29489.3 |
| 42 | 4533.6 | 92 | 13488.3 | 142 | 22882.0 | 192 | 29559.6 |
| 43 | 4689.7 | 93 | 13680.8 | 143 | 23054.8 | 193 | 29625.0 |
| 44 | 4847.3 | 94 | 13873.4 | 144 | 23226.6 | 194 | 29685.1 |
| 45 | 5006.2 | 95 | 14066.2 | 145 | 23397.4 | 195 | 29739.3 |
| 46 | 5166.4 | 96 | 14259.1 | 146 | 23567.1 | 196 | 29786.9 |
| 47 | 5328.0 | 97 | 14452.0 | 147 | 23735.8 | 197 | 29826.7 |
| 48 | 5490.7 | 98 | 14645.0 | 148 | 23903.3 | 198 | 29856.5 |
| 49 | 5654.7 | 99 | 14838.0 | 149 | 24069.7 | | |
| 50 | 5819.9 | 100 | 15030.3 | 150 | 24234.9 | | |

Tabellenzahlen rechnerisch ermittelt, für amtliche Zwecke nicht geeignet. Aufgrund der üblichen Toleranzen und der unterschiedlichen Einbaubedingungen Abweichungen bis zu 6% möglich.

